

HANDLE TRIMS

DD2

ITEM NO.	PART NUMBER	QTY.
1	DD2-ESC-RING	1
2	DD2-ESC	1
3	SL-LVR	1
4	TR24-STEM	1
5	AS568 - 012	1
6	.497x.391x.02-PLSTC-WSHR	1
7	CR-FHMS 0.164-32x1.25x1.25-S	1

DD3

ITEM NO.	PART NUMBER	QTY.
1	DD2-ESC-RING	1
2	DD2-ESC	1
3	SX-CRSS-HNDL	1
4	TR24-STEM	1
5	AS568 - 012	1
6	.497x.391x.02-PLSTC-WSHR	1
7	CR-FHMS 0.164-32x1.25x1.25-S	1

Specification from Finished Wall to Tip of Broach Stem

HANDLE TRIM #	MEASUREMENT (IN.)
DD2/DD3	1 3/8"

Note: When fitting handle it may be necessary to shorten broach stem and/or threaded nipple to eliminate gap between handle and escutcheon

IMPORTANT INSTALLATION INFORMATION

- USE TEFLON TAPE OR PIPE SEALANT FOR THREADED CONNECTIONS
- DO NOT USE PLUMBER'S PUTTY ON ANY OF THE BRASS COMPONENTS
This will cause the finish to tarnish and void the warranty. A non-corrosive Alkoxy Silicone is recommended.
- DURING SWEATING OF LINES DO NOT OVERHEAT CASTING
Overheating may cause damage to internal mechanism
- COPPER ADAPTORS MAY BE REQUIRED TO COMPLETE YOUR INSTALLATION

For technical support, please call 718-257-2800